



DIN EN 22 568

HOBBY NO/CS/WS
code 211 XXX

STANDARD HSS
code 241 XXX

STANDARD HSS
code 271 XXX

Závitové kruhové čelisti Circular dies Schneideisen Плашки



Whitworthův závit BS-84:1956
Whitworth thread BS-84:1956
Whitworth-Gewinde BS-84:1956
Резьба Витворта BS-84:1956

Licování: střední / Tolerance: medium class /
Toleranz: Mittelklasse / Подгонка: средний класс



1,5P

	z/1"	P	ØD	h	S		code ^{x)}
BSW 1/16"	60	0,423	16	5	3	1,50	XXX 116
BSW 3/32"	48	0,529	16	5	3	2,30	XXX 332
BSW 1/8"	40	0,635	20	5	3	3,10	XXX 180
BSW 5/32"	32	0,794	20	5	3	3,88	XXX 532
BSW 3/16"	24	1,058	20	7	3	4,66	XXX 316
BSW 7/32"	24	1,058	20	7	4	5,46	XXX 732
BSW 1/4"	20	1,270	20	7	4	6,24	XXX 140
BSW 5/16"	18	1,411	25	9	4	7,82	XXX 516
BSW 3/8"	16	1,588	30	11	4	9,40	XXX 380
BSW 7/16"	14	1,814	30	11	5	10,98	XXX 716
BSW 1/2"	12	2,117	38	14	4	12,56	XXX 120
BSW 9/16"	12	2,117	38	14	5	14,14	XXX 916
BSW 5/8"	11	2,309	45	18	5	15,72	XXX 580
BSW 3/4"	10	2,540	45	18	5	18,89	XXX 340
BSW 7/8"	9	2,822	55	22	5	22,10	XXX 780
BSW 1"	8	3,175	55	22	6	25,27	XXX 100
BSW 1 1/8"	7	3,629	65	25	6	28,44	XXX 118
BSW 1 1/4"	7	3,629	65	25	7	31,61	XXX 114
BSW 1 3/8"	6	4,233	65	25	7	34,77	XXX 138
BSW 1 1/2"	6	4,233	75	30	7	37,95	XXX 112
BSW 1 5/8"	5	5,080	75	30	8	41,11	XXX 158
BSW 1 3/4"	5	5,080	90	36	7	44,28	XXX 134
BSW 1 7/8"	4,5	5,644	90	36	7	47,30	XXX 178
BSW 2"	4,5	5,644	90	36	8	50,62	XXX 200

x) 211 XXX - NO / CS / WS

x) 241 XXX - HSS

x) 271 XXX - HSS s lamačem třísek / with spiral point / mit Schälanschnitt / с лопателем стружек



BUČOVICE TOOLS a.s.

*Materiál: NO; HSS
- dle požadavku
Provedení: závit lapovaný
do BSW 1"
Závit: pravý*

*Material: CS-carbon steel;
HSS - on request
Execution: lapped thread
to BSW 1"
Thread: right-hand*

*Werkstoff: WS-Werkzeugstahl;
HSS - nach dem Anspruch
Ausführung: geläpptes
Gewinde bis BSW 1"
Gewinde: rechts*

*Материал: NO-инструментальная сталь; HSS - по заказу
Изготовлено: резьба шлифованная до BSW 1"
Резьба: правая*