







PN 8/3225**HOBBY NO/CS/WS**
code 230 XXX**STANDARD HSS**
code 260 XXX**Závitové kruhové
čelisti
Circular dies
Schneideisen
Плашки**Lícování: 6g / Tolerance: 6g /
Toleranz: 6g / Подгонка: 6g

1,5P

MMetrický závit ISO DIN 13
Standard metric thread ISO DIN 13
Metrische Regelgewinde ISO DIN 13
Метрическая резьба ISO DIN 13**MF**Jemný metrický závit ISO DIN 13
Fine metric thread ISO DIN 13
Metrische Feingewinde ISO DIN 13
Мелкая метрическая резьба ISO DIN 13

	P	ØD	h	S		code NO/CS	code HSS
M 3	0,5	25	9	3	2,92	230 030	260 030
M 4	0,7	25	9	3	3,91	230 040	260 040
M 5	0,8	25	9	4	4,90	230 050	260 050
M 6	1	25	9	4	5,88	230 060	260 060
M 7	1	25	9	4	6,90	230 070	260 070
M 8	1,25	25	9	4	7,87	230 080	260 080
M 8	1	25	9	4	7,88	230 081	260 081
M 10	1,5	25	9	5	9,85	230 100	260 100
M 10	1	25	9	5	9,88	230 101	260 101
M 12	1,75	25	9	5	11,83	230 120	260 120
M 12	1,5	25	9	5	11,85	230 121	260 121
M 12	1	25	9	5	11,88	230 122	260 122
M 16	2	38	14	6	15,82	230 160	260 160
M 20	2,5	38	14	8	19,79	230 200	260 200

Materiál: NO: HSS
Provedení: závit lapaný
Závit: pravýMaterial: CS-carbon steel;
HSS
Execution: lapped thread
Thread: right-handWerkstoff: WS-Werkzeugstahl; HSS
Ausführung: geläpptes Ge-
winde
Gewinde: rechtsМатериал: NO-инструмен-
тальная сталь; HSS
Изготовлено: резьба
Резьба: правая**DIN EN 22 568****HOBBY NO/CS/WS**
code 213 XXX**STANDARD HSS**
code 243 XXX**STANDARD HSS**
code 273 XXX**Závitové kruhové
čelisti
Circular dies
Schneideisen
Плашки**

1,5P

PgPancéřový závit DIN 40430
Steel conduit thread DIN 40430
Stahlpanzerrohr-Gewinde DIN 40430
Панцирная резьба DIN 40430

	z/1"	P	ØD	h	S		code NO/CS	code HSS	code HSS ^{x)}
Pg 7	20	1,270	38	10	4	12,40	213 070	243 070	273 070
Pg 9	18	1,411	45	14	5	15,10	213 090	243 090	273 090
Pg 11	18	1,411	45	14	5	18,50	213 110	243 110	273 110
Pg 13,5	18	1,411	45	14	6	20,30	213 135	243 135	273 135
Pg 16	18	1,411	55	16	5	22,40	213 160	243 160	273 160
Pg 21	16	1,588	65	18	7	28,15	213 210	243 210	273 210
Pg 29	16	1,588	75	20	7	36,85	213 290	243 290	273 290
Pg 36	16	1,588	90	22	8	46,85	213 360	243 360	273 360
Pg 42	16	1,588	105	22	10	53,85	213 420	243 420	273 420
Pg 48	16	1,588	105	22	10	59,15	213 480	243 480	273 480

^{x)} HSS s lamačem třísek / with spiral point / mit Schälanschnitt / с ломателем стружекMateriál: NO: HSS
- dle požadavku
Provedení: standardní
Závit: pravýMaterial: CS-carbon steel;
HSS - on request
Execution: standard
Thread: right-handWerkstoff: WS-Werkzeugstahl;
HSS - nach dem Anspruch
Ausführung: normal
Gewinde: rechtsМатериал: NO-инструмен-
тальная сталь; HSS
- по заказу
Изготовлено: стандартно
Резьба: правая**BUČOVICE
TOOLS a.s.****M / MF / Pg 39**