




# BS-1127:1950

STANDARD HSS  
code 440 XXX

**Závitové kruhové  
čelisti stavitelné**  
**Circular adjustable dies**  
**Runde Schneideisen geschlitzt**  
**Плашки регулируемые**




M  
Metrický závit ISO DIN 13  
Standard metric thread ISO DIN 13  
Metrische Regelgewinde ISO DIN 13  
Метрическая резьба ISO DIN 13

MF  
Jemný metrický závit ISO DIN 13  
Fine metric thread ISO DIN 13  
Metrische Feingewinde ISO DIN 13  
Мелкая метрическая резьба ISO DIN 13

Licování: 6g / Tolerance: 6g /  
Toleranz: 6g / Подгонка: 6g



1,5P

P	ØD - A=13/16"	ØD - B=1"	ØD - C=1 5/16"	ØD - D=1 1/2"	ØD - E=2"	ØD - G=3"		code(x)
	S	S	S	S	S	S		
M 2	0,4	3					1,93	440 020X
M 3	0,5	3	3				2,92	440 030X
M 3,5	0,6	3	3				2,94	440 035X
M 4	0,7	3	3				3,91	440 040X
M 4	0,5	3	3				3,93	440 041X
M 5	0,8	4	4				4,90	440 050X
M 5	0,5	4	4				4,93	440 051X
M 6	1	4	4	4			5,88	440 060X
M 6	0,75	4	4	4			5,91	440 061X
M 7	1	4	4	4			6,88	440 070X
M 7	0,75	4	4	4			6,90	440 071X
M 8	1,25	4	4	4	4		7,87	440 080X
M 8	1	4	4	4	4		7,88	440 081X
M 9	1,25	4	4	4	4		8,87	440 090X
M 10	1,5	5	4	4	4		9,85	440 100X
M 10	1,25	5	4	4	4		9,86	440 101X
M 10	1	5	4	4	4		9,88	440 102X
M 11	1,5		5	5			10,85	440 110X
M 12	1,75		5	4	4		11,83	440 120X
M 12	1,5		5	4	4		11,85	440 121X
M 12	1,25		5	4	4		11,86	440 122X
M 12	1		5	4	4		11,88	440 123X
M 14	2			5	5		13,82	440 140X
M 14	1,5			5	5		13,86	440 141X
M 14	1,25			5	5		13,88	440 142X
M 16	2			5	5		15,82	440 160X
M 16	1,5			5	5		15,85	440 161X
M 18	2,5				5		17,79	440 180X
M 18	1,5				5		17,85	440 182X
M 20	2,5				6		19,79	440 200X
M 20	1,5				6		19,85	440 202X
M 22	2,5				6		21,79	440 220X
M 22	1,5				6		21,85	440 221X
M 24	3				6		23,76	440 240X
M 24	2				6		23,82	440 241X
M 24	1,5				6		23,85	440 242X
M 25	1,5				6		24,85	440 251X
M 27	3					6	26,76	440 270X
M 30	3,5					6	29,73	440 300X
M 33	3,5					6	32,73	440 330X
M 36	4					6	35,70	440 360X
M 39	4					6	38,70	440 390X

- x) 440 XXXA (13/16" - 20,6 mm, h = 6,35)
- x) 440 XXXB (1" - 25,4 mm, h = 9,5)
- x) 440 XXXC (1 5/16" - 33,4 mm, h = 11,1)
- x) 440 XXXD (1 1/2" - 38,1 mm, h = 12,7)
- x) 440 XXXE (2" - 50,8 mm, h = 15,9)
- x) 440 XXXG (3" - 76,2 mm, h = 22,2)



**BUČOVICE  
TOOLS a.s.**

Materiál: HSS  
Provedení: závit lapovaný  
do M 26  
Závit: pravý

Material: HSS  
Execution: lapped thread  
to M 26  
Thread: right-hand

Werkstoff: HSS  
Ausführung: geläpftes  
Gewinde bis M 26  
Gewinde: rechts

Материал: HSS  
Изготовлено: резьба  
шлифованная до M 26  
Резьба: правая