



BS-1127:1950

STANDARD HSS
code 441 XXX

**Závitové kruhové
čelisti stavitelné**
Circular adjustable dies
Runde Schneideisen
geschlitzt
Плашки регулируемые




Whitworthův závit BS 84:1956
Whitworth thread BS 84:1956
Whitworth-Gewinde BS 84:1956
Резьба Витворта BS 84:1956

Licování: střední / Tolerance: medium class /
Toleranz: Mittelklasse / Подгонка: средний класс



1,5P



	z/1"	P	ØD - A=13/16" S	ØD - B=1" S	ØD - C=1 5/16" S	ØD - D=1 1/2" S	ØD - E=2" S		code ^{x)}
BSW 3/32"	48	0,529	3					2,30	441 332X
BSW 1/8"	40	0,635	3					2,10	441 180X
BSW 5/32"	32	0,794	3					3,88	441 532X
BSW 3/16"	24	1,058	3					4,66	441 316X
BSW 1/4"	20	1,270	4					6,24	441 140X
BSW 5/16"	18	1,411		4				7,82	441 516X
BSW 3/8"	16	1,588		4				9,40	441 380X
BSW 7/16"	14	1,814			4	4		10,98	441 716X
BSW 1/2"	12	2,117			5	5		12,56	441 120X
BSW 9/16"	12	2,117			4	4		14,14	441 916X
BSW 5/8"	11	2,309				5	5	15,72	441 580X
BSW 3/4"	10	2,540				5	5	18,89	441 340X
BSW 7/8"	9	2,822					5	22,10	441 780X
BSW 1"	8	3,175					6	25,27	441 100X

x) 441 XXXA (13/16" - 20,6 mm, h = 6,35)

x) 441 XXXB (1" - 25,4 mm, h = 9,5)

x) 441 XXXC (1 5/16" - 33,4 mm, h = 11,1)

x) 441 XXXD (1 1/2" - 38,1 mm, h = 12,7)

x) 441 XXXE (2" - 50,8 mm, h = 15,9)



**BUČOVICE
TOOLS a.s.**

Materiál: HSS
Provedení: závit lapovaný do
BSW 1"
Závit: pravý

Material: HSS
Execution: lapped thread
to BSW 1"
Thread: right-hand

Werkstoff: HSS
Ausführung: geläpftes
Gewinde bis BSW 1"
Gewinde: rechts

Материал: HSS
Изготовлено: резьба
шлифованная до BSW 1"
Резьба: правая