



BS-1127:1950

STANDARD HSS
code 442 XXX

**Závitové kruhové
čelisti stavitelné**
Circular adjustable dies
Runde Schneideisen
geschlitz
Плашки регулируемые



Trubkový závit DIN ISO 228
Pipe thread DIN ISO 228
Rohrgewinde DIN ISO 228
Трубная резьба DIN ISO 228

Lícování: A / Tolerance: A /
Toleranz: A / Подгонка: A



1,5P

G(BSP)

	z/1"	P	ØD - B=1" S	ØD - C=1 5/16" S	ØD - D=1 1/2" S	ØD - E=2" S	ØD - G=3" S	ØD - I=4" S	Ød	code x)
G 1/16	28	0,907	4	4					7,62	442 116X
G 1/8"	28	0,907	5	4	4				9,62	442 180X
G 1/4"	19	1,337			5	5			13,03	442 140X
G 3/8"	19	1,337			5	5			16,54	442 380X
G 1/2"	14	1,814			6	6			20,81	442 120X
G 5/8"	14	1,814				6			22,77	442 580X
G 3/4"	14	1,814				6			26,30	442 340X
G 1"	11	2,309					6		30,06	442 100X
G 1 1/4"	11	2,309					8		33,07	442 114X
G 1 1/2"	11	2,309					9		41,73	442 112X
G 2"	11	2,309						8	47,62	442 200X

- x) 442 XXXB (1" - 25,4 mm, h = 9,5)
- x) 442 XXXC (1 5/16" - 33,4 mm, h = 11,1)
- x) 442 XXXD (1 1/2" - 38,1 mm, h = 12,7)
- x) 442 XXXE (2" - 50,8 mm, h = 15,9)
- x) 442 XXXG (3" - 76,2 mm, h = 22,2)
- x) 442 XXXI (4" - 101,6 mm, h = 25,4)

Materiál: HSS
Provedení: závit lapovaný
do G 3/4"
Závit: pravý

Material: HSS
Execution: lapped thread to
G 3/4"
Thread: right-hand

Werkstoff: HSS
Ausführung: geläpptes
Gewinde bis G 3/4"
Gewinde: rechts

Материал: HSS
Изготовлено: резьба
шлифованная до G 3/4"
Резьба: правая

 **BUČOVICE
TOOLS a.s.**

